

VENTILATING FAN

ELECTRIC SHUTTER FAN

- ◆ First class ABS & PP material
- ◆ Silicon steel motor with built-in thermo-cut-off protection
- ◆ Big air flow and quite
- ◆ Easy installation for glass and wall

SPECIFICATIONS:

Model	Size(Inch)	Watts	Voltage	Air Delivery	Speed	Current
KBE15E16"	6"	23W	220-240V	240m3/h	1300r/min	0.13A
KBE20E18"	8"	28W	50/60Hz - T45	360m3/h	1250r/min	0.15A



CEILING DUCT EXHAUST FAN

- ◆ First class ABS material
- ◆ Silicon steel motor with built-in thermo-cut-off protection
- ◆ Advanced blade design for high air volume and low noise level
- ◆ Easy installation for glass and ceiling.

SPECIFICATIONS:

Model	Size (Inch)	Rated Voltage	Rated Frequency	Rated Power	Air Delivery	Noise
		[V]	[Hz]	[W]	[M3/h]	[dB]
KBE10C	4"	220-240	50/60	13	58	40
KBE15C	6"	220-240	50/60	22	162	45



CEILING DUCT EXHAUST FAN

- ◆ First class ABS material
- ◆ Silicon steel motor with built-in thermo-cut-off protection
- ◆ Advanced blade design for high air volume and low noise level
- ◆ Easy installation for glass and ceiling.

SPECIFICATIONS:

Model	Size (Inch)	Rated Voltage	Rated Frequency	Rated Power	Air Delivery	Noise
		[V]	[Hz]	[W]	[M3/h]	[dB]
KBAPT20A	8"	220-240	50/60	23	258	47
KBAPT25A	10"	220-240	50/60	28	432	49

