

# VENTILATING FAN

ESMA  
&  
GMARK  
Approved

## WINDOW MOUNTED EXHAUST FAN - ROUND

- ◆ First class plastic PP material
- ◆ Silicon steel motor with built-in thermo-cut-off protection
- ◆ Advanced blade design for high air volume and low noise level
- ◆ Easy installation for glass and wall

### SPECIFICATIONS:

Model	Rated Voltage	Rated Frequency	Rated Power	Air Delivery	Noise
	[V]	[Hz]	[W]	[M3/h]	[dB]
KBEF15G(6")	220-240	50/60	15	260	37
KBEF20G(8")	220-240	50/60	20	320	40



## WINDOW MOUNTED EXHAUST FAN - SQUARE

- ◆ First class plastic PP material
- ◆ Silicon steel motor with built-in thermo-cut-off protection
- ◆ Advanced blade design for high air volume and low noise level
- ◆ Easy installation for glass and wall

### SPECIFICATIONS:

Model	Rated Voltage	Rated Frequency	Rated Power	Air Delivery	Noise
	[V]	[Hz]	[W]	[M3/h]	[dB]
KBE15A(6")	220-240	50/60	23	258	39
KBE20A(8")	220-240	50/60	28	480	44
KBE25A(10")	220-240	50/60	38	720	45
KBE30A(12")	220-240	50/60	48	1100	48



## AUTO SHUTTER FAN

- ◆ First class ABS material
- ◆ Silicon steel motor with built-in thermo-cut-off protection
- ◆ Big air flow and quite
- ◆ Easy installation for glass and wall
- ◆ Automatic thermo-actuator for shutter open/close

### SPECIFICATIONS:

Model	Voltage	Input (W)	Air-Flow (m³/h)	Noise (dB)	Size (mm)
KBAF15	220-240	22	220	37	150
KBAF23	220-240	40	520	40	230

